



WRIGLEY BRICK COLLECTION OPTIONS

COLORS:



FINISH: MATTE

SIZE:







WRIGLEY BRICK PERFORMANCE DATA



















Stoneware

Substantial Variation

Compliant

Thickness 8mm

V.O.C.

Frost Proof

Made/Stock Absorption

Technical Feature	Method	Value Required ASNI A 137.1	Studio Collection Results
Facial Dimension	ASTM C-499	± 0.25% or ± 0.03 in	Comply
Wedging	ASTM C-502	± 0.25% or ± 0.03 in	Comply
Warpage Diagonal	ASTM C-485	± 0.4% or 0.07 in	Comply
Warpage Edge	ASTM C-485	± 0.4% or 0.05 in	Comply
Thickness	ASTM C-499	Range: 0.040 inch max	Comply
Water Absorption	ASTM C-373	≤ 0.5%	≤ 0.6%
Breaking Strength	ASTM C-648	≥ 250 lbs (≥ 1113N)	≥ 250 lbs (≥ 1113N)
Freeze Thaw	ASTM C-1026	No damages	N/A
Chemical Resistance	ASTM C-650	As reported	Comply
Dynamic Coefficient of Friction	ANSI A 326.3	≥ 0.42	≥ 0.42

WRIGLEY BRICK



