



ONDA

ONDA is the stunning embodiment of the beauty and power of nature. Four dynamic colors flow across ONDA, creating a contemporary range that is both elegant and versatile and is sure to compliment any commercial space.

CZ03-03M

ONDA COLLECTION OPTIONS

COLORS:




CZ03-01M



CZ03-02M



CZ03-03M



CZ03-04M

FINISH: MATTE


SIZE:




12" x 24"



6" x 24"



24" x 24"




24" x 48"

DECORS:



2" x 24"
on 12" x 24" sheet



2" x 2" Mosaic
on 12" x 12" sheet

TRIMS:




3" x 24"
Bullnose



CZ03-04M

ONDA

PERFORMANCE DATA



Porcelain
Stoneware



Floor



Wall



Slight
Variation




DCOF
Compliant



Thickness
9mm



Rectified
Tile



No
V.O.C.



Frost
Proof



Low Water
Absorption



USA
Made/Stock

Technical Feature	Method	Value Required ANSI A 137.1	Studio Collection Results
Facial Dimension	ASTM C-499	$\pm 0.25\%$ or ± 0.03 in	In accordance with ANSI A 137.1
Wedging	ASTM C-502	$\pm 0.25\%$ or ± 0.03 in	In accordance with ANSI A 137.1
Warpage diagonal	ASTM C-485	$\pm 0.4\%$ or 0.07 in	In accordance with ANSI A 137.1
Warpage edge	ASTM C-485	$\pm 0.4\%$ or 0.05 in	In accordance with ANSI A 137.1
Thickness	ASTM C-499	Range: 0.040 inch max	In accordance with ANSI A 137.1
Water absorption	ASTM C-373	$\leq 0.5\%$	Passed "impervious tiles" Class P1
Breaking strength	ASTM C-648	≥ 250 lbs (≥ 1113 N)	≥ 400 lbs
Freeze thaw	ASTM C-1026	No damages	No damages
Chemical Resistance	ASTM C-650	As reported	Unaffected
Dynamic Coefficient of Friction	ANSI A 326.3	≥ 0.42	≥ 0.42

ONDA

